



## รุ่น MK Series (new)

### MK Series ,Mk2100/Mk1100

The beauty of print, Speedy, Ease of use Meet the all requirements of the Cable ID Marking



## รุ่น M-1 Std.

### Specification

M-1 Std.	
Printing method	Thermal transfer
Resolution	300dpi
Printing speed	12.5 mm/s
Output rate	21 pcs./min.
Ink ribbons	Exclusive cassette. Black: 100m; White: 85m
Character sizes	2mm, 3mm, 6mm, (full-width, half-width available for each).
Font	Canon Semiconductor Equipment Original
Input modes	Roman alphanumeric, Symbol input
Display	LCD Graphic (160 x 64 dots)
Display capacity	10 characters / line x 2 lines (full-width)
Built-in memory	Printing data: Approx. 2,500 characters Files: Approx. 7,500 characters Service life of internal backup battery for data storage: About 5 years
Media cutting method	Automatic full-cutting, Automatic half-cutting
Power supply	Exclusive AC Adapter Input voltage: AC 100V-240V 50/60 Hz
Operating environment	15°C - 32.5°C (59°F - 90.5°F), 10% - 85% RH Range is lowered to 5°C (41°F) with Tube Warmer option installed.
Storage environment	5°C -32.5°C (41°F - 90.5°F), 10% - 85% RH
Dimensions (W x D x H)	250 x 300 x 85 mm (9.8 x 11.8 x 3.4 in.)
Weight	2kg (4.4 lb.) (printer only)

## Print Media

Tubing	Commercial PVC Tubing, $\phi$ 2.5 - 5.2 mm, 0.5 mm thick (Other tubes should be tested for printing.)
Label Tape	Exclusive cassettes (White, Yellow, Silver) Width: 6 mm, 9 mm, 12 mm, Length 30 m (Silver: 27 m)
Wrap Around Tape	Exclusive cassettes Print area onl: White, Other areas: Transparent Take-up length: 8 m Length: 33 mm Width: 8-150 mm (depends on cut setting)
Heat Shrink Tubing	Exclusive cassettes (White, Yellow) Shrink ratio: 3:1, $\phi$ 3 mm, $\phi$ 6 mm, length 5 m Shrink ratio: 2:1, $\phi$ 32. mm, 4.8 mm, 6.4 mm, length: 5 m

## Consumables

Product Code	Product Names	Product Code	Product Names
3476A036	Ribbon Cassette Black (100m)	3476A042	Cutter Set
3476A037	Ribbon Cassette White (85m)	3476A043	Cleaner Set for Tubu Attachment
3476A023	Label Tape Cassette6mm x 30m (White)	3476A071	Cleaner Set for Tube Warmer
3476A024	Label Tape Cassette9mm x 30m (White)	3476A049	Heat Shrink Tube3:1 3mm x 5m (Yellow)
3476A025	Label Tape Cassette12mm x 30m (White)	3476A048	Heat Shrink Tube3:1 3mm x 5m (White)
3476A026	Label Tape Cassette6mm x 30m (Yellow)	3476A051	Heat Shrink Tube3:1 6mm x 5m (Yellow)
3476A027	Label Tape Cassette9mm x 30m (Yellow)	3476A050	Heat Shrink Tube3:1 6mm x 5m (White)
3476A028	Label Tape Cassette12mm x 30m (Yellow)	3476A030	Heat Shrink Tube3:1 3.2mm x 5m (Yellow)
3476A068	Label Tape Cassette6mm x 27m (Silver)	3476A029	Heat Shrink Tube2:1 3.2mm x 5m (White)
3476A069	Label Tape Cassette9mm x 27m (Silver)	3476A032	Heat Shrink Tube2:1 4.8mm x 5m (Yellow)
3476A070	Label Tape Cassette12mm x 27m (Silver)	3476A031	Heat Shrink Tube2:1 4.8mm x 5m (White)
3476A075	Wrap Around Tape33mm x 8m (White)	3476A034	Heat Shrink Tube2:1 6.4mm x 5m (Yellow)
		3476A033	Heat Shrink Tube2:1 6.4mm x 5m (White)

## Option

Product Code	Product Names	Compatible Printer
3476A029	Tube Warmer Set	M-1 Pro II/Std.
3476A030	Tube Feeder Set	M-1 Pro II
3476A032	Transport Auxiliary Guide for Wrap Around Tape	M-1 Pro II/Std.
3476A035	PC Connection Kit II	M-1 Pro II
3476A025	Hard Case	M-1 Pro II/Std.
3476A044	Soft Case	M-1 Pro II
3476A033	Plate Attachment	M-1 Pro II/Std.
3476A046	Tube Attachment	M-1 Pro II/Std.

# รุ่น **M-1 Pro II**

## Specification

<b>M-1 Pro II</b>	
Printing method	Thermal transfer
Resolution	300dpi
Printing speed	Tubes: High Speed 25 mm/s, Standard 18.5 mm/s Labels: 25 mm/s
Output rate	High Speed Mode: 35 pcs./min. Standard Mode: 30 pcs./min. (Printing characters on tubing, half-cutting 20 mm segments, standard cutting strength)
Ink Ribbons	Exclusive cassette. Black: 100m; White: 85m
Character sizes	2mm, 3mm, 6mm, (full-width, half-width available for each).
Font	Canon Semiconductor Equipment Original
Input modes	Alphanumeric, Symbol input
Display	LCD Graphic (160 x 64 dots)
Display capacity	10 characters / line x 2 lines (full-width)
Built-in memory	Printing data: Approx. 2,500 characters Files: Approx. 7,500 characters Service life of internal backup battery for data storage: About 5 years
Media cutting method	Automatic full-cutting, Automatic half-cutting
Power supply	Exclusive AC Adapter Input voltage: AC 100V-240V 50/60 Hz
Operating environment	15°C - 32.5°C (59°F - 90.5°F), 10% - 85% RH Range is lowered to 5°C (41°F) with Tube Warmer option installed.
PC interface	Parallel (IEEE 1284 Standard), Exclusive PC Connection Kit (option) USB 1.1 compatible
Storage environment	5°C -32.5°C (41°F - 90.5°F), 10% - 85% RH
Dimensions (W x D x H)	250 x 300 x 85 mm (9.8 x 11.8 x 3.4 in.)
Weight	2kg (4.4 lb.) (printer only)

## Print Media

Tubing	Commercial PVC Tubing, $\phi$ 2.5 - 5.2 mm, 0.5 mm thick (Other tubes should be tested for printing.)
Label Tape	Exclusive cassettes (White, Yellow, Silver) Width: 6 mm, 9 mm, 12 mm, Length 30 m (Silver: 27 m)
Wrap Around Tape	Exclusive cassettes Print area only: White, Other areas: Transparent Take-up length: 8 m Length: 33 mm Width: 8-150 mm (depends on cut setting)
Plates	Specified thickness: 0.5 mm Plates of other thickness should be tested for printing. Width: 8 mm, 8.5 mm, 9 mm, 9.5 mm, 10 mm Plate Attachment option is required. Cutting on the printer is not possible.
Heat Shrink Tubing	Exclusive cassettes (White, Yellow) Shrink ratio: 3:1, $\phi$ 3 mm, $\phi$ 6 mm, length 5 m Shrink ratio: 2:1, $\phi$ 3.2 mm, 4.8 mm, 6.4 mm, length: 5 m

## Consumables

Product Code	Product Names	Product Code	Product Names
3476A036	Ribbon Cassette Black (100m)	3476A042	Cutter Set
3476A037	Ribbon Cassette White (85m)	3476A043	Cleaner Set for Tubu Attachment
3476A023	Label Tape Cassette6mm x 30m (White)	3476A071	Cleaner Set for Tube Warmer
3476A024	Label Tape Cassette9mm x 30m (White)	3476A049	Heat Shrink Tube3:1 3mm x 5m (Yellow)
3476A025	Label Tape Cassette12mm x 30m (White)	3476A048	Heat Shrink Tube3:1 3mm x 5m (White)
3476A026	Label Tape Cassette6mm x 30m (Yellow)	3476A051	Heat Shrink Tube3:1 6mm x 5m (Yellow)
3476A027	Label Tape Cassette9mm x 30m (Yellow)	3476A050	Heat Shrink Tube3:1 6mm x 5m (White)
3476A028	Label Tape Cassette12mm x 30m (Yellow)	3476A030	Heat Shrink Tube3:1 3.2mm x 5m (Yellow)
3476A068	Label Tape Cassette6mm x 27m (Silver)	3476A029	Heat Shrink Tube2:1 3.2mm x 5m (White)
3476A069	Label Tape Cassette9mm x 27m (Silver)	3476A032	Heat Shrink Tube2:1 4.8mm x 5m (Yellow)
3476A070	Label Tape Cassette12mm x 27m (Silver)	3476A031	Heat Shrink Tube2:1 4.8mm x 5m (White)
3476A075	Wrap Around Tape33mm x 8m (White)	3476A034	Heat Shrink Tube2:1 6.4mm x 5m (Yellow)
		3476A033	Heat Shrink Tube2:1 6.4mm x 5m (White)

## Option

Product Code	Product Names	Compatible Printer
3476A029	Tube Warmer Set	M-1 Pro II/Std.
3476A030	Tube Feeder Set	M-1 Pro II
3476A032	Transport Auxiliary Guide for Wrap Around Tape	M-1 Pro II/Std.
3476A035	PC Connection Kit II	M-1 Pro II
3476A025	Hard Case	M-1 Pro II/Std.
3476A044	Soft Case	M-1 Pro II
3476A033	Plate Attachment	M-1 Pro II/Std.
3476A046	Tube Attachment	M-1 Pro II/Std.